

Regrinding Service – delivery note for regrind articles

Please enclose the completed form in the **regrinding box** !


Company:	Department
Technical Sales Engineer:	Contact:
Customer no.:	Contact Tel. No.:
your order number	Contact E-Mail:

Drills, NC spot drills and stepped drills



Drills are reground on the main cutting edges and coated with original coating if possible.
 Drills are reduced depending on the amount of wear and ground as new.
Stepped drills are also ground on the countersink angle.

Standard process				special order
Position	Article no. (New article)	No. of pieces	Main cutting edge + Chamfer if required + Original coating	Comment
1			<input checked="" type="checkbox"/>	
2			<input checked="" type="checkbox"/>	
3			<input checked="" type="checkbox"/>	
4			<input checked="" type="checkbox"/>	
5			<input checked="" type="checkbox"/>	
6			<input checked="" type="checkbox"/>	
7			<input checked="" type="checkbox"/>	
8			<input checked="" type="checkbox"/>	
9			<input checked="" type="checkbox"/>	
10			<input checked="" type="checkbox"/>	
11			<input checked="" type="checkbox"/>	
12			<input checked="" type="checkbox"/>	
13			<input checked="" type="checkbox"/>	
14			<input checked="" type="checkbox"/>	
15			<input checked="" type="checkbox"/>	

 If a regrind is not economically viable, your tools will be returned unprocessed.

 All information about our regrinding service can be found under → [cuttingtools/gb/en/regrinding](https://cuttingtools.ceratizit.com)