

Form

Request for special tools

Driven tools

Please send the completed form to support.tsc-china@kometwnt.com!

Company:	Department:
Technical Sales Engineer:	Contact:
Customer no.:	Contact Tel. No.:
Your reference:	Contact E-Mail:

1 Details of the machine

Machine type (e.g. Gildemeister)				Model (e.g. CTX 400)	
Direction of operation	Main spindle (MS)	Sub spindle (SS)	Both (double sided)		
Shank type & size (e.g. VDI 40 to DIN 69880, Ø 40 for Mazak)					
Turret manufacturer (e.g. Sauter, Duplomatic)					
Turret type	Disc turret	Star turret	Nominal height		
Turret model number (e.g. Sauter 05.473.516)					
Number of mounting positions (e.g. 12/16/25)	 of which driven				
Turret drive	Castleated shaft e.g. Duplomatic, DIN 1809  Spline shaft e.g. Sauter, DIN 5480/5482  Bevel shaft e.g. GDM, Traub TNS 60  Castleated shaft e.g. Okuma, Baruffaldi  				

2 Details of the application

Drilling	Milling	Thread cutting
Universal	Quick change system	

3 Details of the Driven Tool

Type	axial		Piece					
	radial -right-		Piece	radial offset -right-		Piece	Angle adjustable ± 105°	Piece
	radial -left-		Piece	radial offset -left-		Piece	Others (e.g. double sided)	Piece
Spindle nose tooling type (e.g. ER16/PRECI-FLEX®)	ER		Solidfix	Modifix	PRECI-FLEX®	Varia VX		
Cooling agent supply	without thro' coolant		with thro' coolant (Note: Filter to < 50 µm)					
Requested special accessories (e.g. Clamping devices with range)								
Others E.g. transmission 1:1 or 1:-1 (reversed direction of rotation)								